A SYMBOLIS A PROMISE.



















Canon


CANON INC. 7-1, Nishi-Shinjuku 2-Chome, Shinjuku-ku, Tokyo 163, Japan Mailing address: P.O. Box 5050, Dai-ichi Seimei Building, Tokyo 163, Japan

USA	CANON_U.S.A., INC. HEADQUARTERS One Canon Plaza, Lake Success, N.Y. 11042, U.S.A.
	CANON U.S.A., INC. MANHATTAN SERVICE CENTER 600 Third Avenue, New York, N.Y. 10016, U.S.A.
	CANON U.S.A., INC. ATLANTA BRANCH 6380 Peachtree Industrial Blvd., Norcross, Georgia 30071, U.S.A.
	CANON U.S.A., INC. CHICAGO BRANCH 100 Park Blvd. Itasca, IL60143-2693, U.S.A.
	CANON U.S.A., INC. LOS ANGELES BRANCH 123 Paularino Avenue East, Costa Mesa, California 92626, U.S.A.
	CANON U.S.A., INC. LOS ANGELES SERVICE CENTER 3321 Wilshire Blvd., Los Angeles, California 90010, U.S.A.
	CANON U.S.A., INC. SANTA CLARA BRANCH 4000 Burton Drive, Santa Clara, California 95054, U.S.A.
	CANON U.S.A., INC. DALLAS OFFICE 3200, Regent Blvd., Irving. Texas 75063-3145, U.S.A.
	CANON U.S.A., INC. HONOLULU OFFICE Bldg. B-2, 1050 Ala Moana Blvd., Honolulu, Hawaii 96814, U.S.A.
CANADAEUROPE, AFRICA	CANON CANADA INC. HEADQUARTERS 6390 Dixie Road, Mississauga, Ontario L5T 1P7, Canada
	CANON CANADA INC. MONTREAL SERVICE CENTRE 10652 Côte de Liesse, Lachine, Quebec H8T 1A5, Canada
	CANON CANADA INC. CALGARY OFFICE 2828, 16th Street, N.E. Calgary, Alberta T2E 7K7, Canada
& MIDDLE EAST	CANON EUROPA N.V. P.O. Box 7907, 1008 AC Amsterdam, The Netherlands
	CANON FRANCE-PHOTO CINEMA S.A. 30, boulevard Vital-Bouhot, ile de la Jatte, 92521 Neuilly-sur-Seine, France
	CANON UK LTD. Units 4 & 5, Brent Trading Centre, North Circular Road, London NW10 OJF, United Kingdom
CENTRAL &	CANON EURO-PHOTO G.m.b.H Linsellesstraße 142-156, D-4156 Willich 3, West Germany
SOUTH AMERICA	CANON LATIN AMERICA, INC. DEPTO. DE VENTAS Apartado 7022, Panamá 5, República de Panamá
	CANON LATIN AMERICA, INC. CENTRO DE SERVICIO Y REPARACION Apartado 2019, Zona Libre de Colón, República de Panamá
SOUTHEAST ASIA_	CANON HONG KONG TRADING CO., LTD. Room 1101-3 & 1121-2, Peninsula Centre, 67 Mody Road, Tsimshatsui East, Kowloon, Hong Kong
	CANON SINGAPORE PTE. LTD. 95 South Bridge Road #13-01/15, South Bridge Centre, Singapore 0105
OCEANIA	CANON AUSTRALIA PTY. LTD. Unit 1/37, Waterloo Road, North Ryde (Macquarie Park), N.S.W. 2113, Australia
JAPAN	CANON SALES CO., INC. 11-28, Mita, 3-Chome, Minato-ku, Tokyo 108, Japan

PUB.C-CE-243A ©CANON INC. 1985 PRINTED IN JAPAN 0486B6

Canon

Aqua Snappy As-6



THE CAMERA THAT GOES WHEREVER THE SPIRIT OF ADVENTURE TAKES YOU

Canon proudly introduces the Aqua Snappy AS-6, the camera that thrives under harsh conditions impossible for other cameras.

Take the AS-6 along on any adventure, from the top of the highest mountain down to 10 meters (33 feet) beneath the sea. Expose it to the harshest conditions: water, sand, dust or snow. Canon's Adventure Camera just keeps on shooting.

The AS-6 may be hard on the outside, but advanced electronics on the inside makes using this 35mm camera as easy as point-and-shoot. Everything is automatic, from film handling and film speed setting to exposure.

Even underwater and close-up photography are easy with the

AS-6's add-on accessories.

And for the adventurer on the move, the AS-6 is the lightest and most compact camera of its kind. So wherever the spirit of adventure takes you, you can take Canon's Adventure Camera.





















THE CAMERA THAT'S ALWAYS IN ITS ELEMENT



A rugged workhorse

The AS-6 is tough—tough enough to stand up to any adventure. The body, constructed of rugged, fiberglass-reinforced polycarbonate resin, is fitted with special rubber protectors for lens and viewfinder. A separate accessory base provides additional protection while serving as a base for add-on accessories. And when the going gets dirty, simply wash the AS-6 off in running water.

WET AND WILD

Weatherproof and waterproof

The Aqua Snappy AS-6 is ready for even the most inhospitable weather and surroundings. Special molding and sealing techniques throughout the AS-6 body and a tough buckle clamp for the back cover prevent any trace of water, snow, dust or sand from working its way into the camera. Film and camera mechanisms are completely protected. In fact, the AS-6 can be submerged as deep as 10 meters (33 feet) underwater with no danger of leakage.



MAKE IT LOOK EASY

Totally automated simplicity

The adventurer has more urgent matters in mind than operating camera controls. That's why the AS-6 is fully automatic—just point the camera where the action is and shoot. Program auto-exposure, fixed focus, auto flash, DX automatic ISO film speed setting and automatic film loading, winding and rewinding make this camera incredibly simple to use. Essential controls are oversized for easy operation even when you're wearing gloves.

BENEATH THE WAVES

Fully equipped for underwater photography

Canon's Adventure Camera is fully equipped to explore the fascinating world of undersea life. Special optics compensate for water's high refractive index while maintaining normal operation out of the water. The frame counter is designed to be clearly visible underwater. A clip-on sports finder suitable for underwater use is standard equipment, and attachments for close-up photography underwater are available. And—naturally—the Aqua Snappy AS-6 floats without special attachments.



TRAVELING LIGHT

Compact and lightweight

The AS-6 is surprisingly lightweight and conveniently compact—good news for the outdoors enthusiast who wants to travel light. At last, there's a tough, waterproof camera that's not too heavy and bulky to stuff into a backpack. You can even wear the AS-6 around your waist in its special carrying bag.





The Aqua Snappy is strong enough to withstand water pressures down to 10 meters (33 feet). And it floats, too.



The Aqua Snappy is hermetically sealed, to keep out dust, sand, grit, or any foreign substance.



The Aqua Snappy is built to operate in adverse condition.



When the red viewfinder lamp flashes to warn of insufficient light, just switch on the flash. The Aqua Snappy will be ready to take flash photos in seconds —even under water.



Accessory Base AS serves as a base for all add-on accessories and as additional protection for the camera.



Simply clip on Close-up Lens AS to take superb detail photos on land or under water.



Close-up Frame AS shows you exactly how to compose a close-up shot on dry land.





Close-up Rod AS measures the exact distance for accurate focus of underwater close-up subjects.



Sports Finder AS allows fast, accurate framing on land or under water—even if you're wearing a diving mask, goggles or other eye protectors.



The bright, buoyant Film Case AS protects 35mm film cartridges from water, sand and dirt.



The attractive Waist Bag for the AS-6 and accessories clips around the waist.

NOMENCLATURE Agua Snappy AS-6 Frame Counter Shutter Button Flash Switch Shutter Button Lock **Exposure Metering Window** Flash Head Battery Viewfinder Release Switch Buckle Lens **Battery Magazine** Sports Finder AS Accessory Base AS

SPECIFICATIONS

Agua Snappy AS-6

TYPE: Weatherproof, fully automatic, 35 mm lens-shutter camera.

FRAME SIZE: 24mm × 36mm.

UNDERWATER DEPTH: 10 meters (33 ft.).

LENS: Construction: 5 elements, 5 groups; Focal length: 35mm on land. 33.6 mm under water; Aperture ratio: f/4.5.

FOCUSING: Fixed at 3m (10ft.) on land: Fixed at 1.5m (5ft.) under water. SHOOTING DISTANCE RANGE: 1.5 m (5 ft.) to infinity on land, 1 m (3.3 ft.) to 3.2m (10.7ft.) under water.

VIEWFINDER: Albada-type reverse Galilean finder, Magnification: 0.45×. Information includes picture frame, center mark, viewfinder lamp (battery check/use flash lamp, red LED).

FILM LOADING: Automatic film loading by aligning leader with positioning mark

FILM WINDING: Automatic.

FILM REWINDING: Rewind starts automatically at end of film, stops automatically when rewind is complete.

BACK COVER: Buckle type

FRAME COUNTER: Additive type; automatically resets to "S" by opening back cover. Counts back with film rewind. Also serves to confirm correct

FILM SPEED: Automatically set by DX code sensor.
AUTOMATIC EXPOSURE COUPLING RANGE: EV10 (f/4.5 at 1/40 sec.) to EV15 (f/11 at 1/250 sec.) with ISO 100 film.

FLASH: Built-in flash.

GUIDE NUMBER: 9 (ISO 100, meters).

AUTO FLASH SHOOTING DISTANCE RANGE: On land: 1.5 m (5ft.) to 3.2 m (10.7 ft.) with ISO 100 negative film; 1.5 m (5 ft.) to 6.4 m (21.3 ft.) with ISO 400 negative film. Under water: 1 m (3.3 ft.) to 2 m (6.7 ft.) with ISO 100 negative film; 1 m (3.3ft.) to 3.2 m (10.7ft.) with ISO 400 negative film. (Depends on clarity of water.)

FLASH RECYCLING TIME: 8 sec. or less (interval between firing of flash and relighting of flash ready lamp) with new alkaline batteries.

BATTERY LIFE: With new alkaline batteries at normal temperatures: without flash, approximately 50 rolls of 24-exp. film. Using flash for each exposure, approximately 5 rolls of 24-exp. film.

POWER SOURCE: Two size-AAA alkaline batteries (LR03).

Ni-Cd batteries cannot be used. BUOYANCY: Floats in water.

VOLUME: 412cm3

DIMENSIONS: $137.5(W) \times 76.5(H) \times 51.5(D) \text{ mm} (5-7/16" \times 3" \times 2")$

WEIGHT: 385g (13-9/16 ozs.) including batteries.

Accessory Base AS

BUOYANCY: Floats in water.

DIMENSIONS: $90(W) \times 93.5(H) \times 53.5(D)$ mm $(3-9/16" \times 3-11/16" \times 2-1/8")$.

WEIGHT: 45q (1-9/16 ozs.).

Sports Finder AS

BUOYANCY: Floats in water.

DIMENSIONS: $85.6(W) \times 72.2(H) \times 25(D) \text{ mm} (3-3/8" \times 2-13/16" \times 1").$

WEIGHT: 22g (3/4 ozs.).

Close-up Lens AS

COMBINED FOCAL LENGTH: 27.1 mm on land, 30.5 mm under water.

SHOOTING DISTANCE: On land: 126mm from film plane.

Field of view: $50.2 \text{mm} \times 73 \text{mm} (2 \text{"} \times 2-7/8 \text{"})$. Under water: 293 mm from film plane. Field of view: $122.8 \text{mm} \times 177.2 \text{mm} (4-13/16 \text{"} \times 7 \text{"})$.

BUOYANCY: Floats in water.

DIMENSIONS: $46(W) \times 55.5(H) \times 20(D) \text{ mm} (1-13/16" \times 2-3/16" \times 13/16").$ WEIGHT: 15g (1/2oz.).

Close-up Frame AS

BUOYANCY: Sinks in water.

DIMENSIONS: 134(W)×121(H)×123(D)mm (5-1/4"×4-3/4"×4-13/16").

WEIGHT: 80g (2-13/16 ozs.).

Close-up Rod AS

BUOYANCY: Floats in water.

DIMENSIONS: 42(W)×66.5(H)×295(D)mm.

 $(1-5/8" \times 2-5/8" \times 11-5/8")$ WEIGHT: 35g (1-1/4ozs.).

Subject to change without notice.